



**Euro Oak Chevron  
Technical Data Sheet**



|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product</b>           | <b>Oak Multilayer Chevron 90mm x 15mm x 510mm Rustic</b>                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Dimensions</b>        | <b>90mm x 15mm x 510mm with a 3mm top layer of European Oak.</b>                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Grading</b>           | <b>Rustic grade. Has knots below 10mm in size brown filled, as well as less than 10% sap wood.</b>                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Construction</b>      | <b>12mm Birch multilayer base for excellent stability, with a 3mm Oak layer from PEFC certified timber.</b>                                                                                                                                                                                                                                                                                                                                                                |
| <b>Guarantee</b>         | <b>Zimbo's Flooring Solutions offers a 5 year guarantee against delamination of the Oak veneer and the cracking or buckling of the floor board subject to normal conditions. This means in an environment with a relative humidity of 40 – 60%. This is subject to product being glued down with Wakol MS 228 adhesive, and Wakol PU 280 moisture barrier when concrete screed residual moisture (measured with Concrete Tramex meter) is above 4.5% moisture content.</b> |
| <b>Formaldehyde</b>      | <b>Emission E1</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Pentachlorophenol</b> | <b>Emission &gt; 5%</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

|                            |                                                                 |
|----------------------------|-----------------------------------------------------------------|
| <b>Underfloor Heating</b>  | <b>Underfloor heating: Temperature compliant to 27 degrees.</b> |
| <b>Installation method</b> | <b>Glue down (according to SAWLF specifications)</b>            |

**2 Panther Park, 11 Berkley Road, Maitland, 7405**

**Tel: +27 21 511 4693**

**Fax: +27 21 511 4694**

**[www.zimbostrading.co.za](http://www.zimbostrading.co.za)**

**[www.loba.co.za](http://www.loba.co.za)**

**[www.wakol.co.za](http://www.wakol.co.za)**

**Reg No: 2002/023222/23**

**Vat No: 424 019 8855**

**Members of C.C.: D.O. Waddy & H.A du Toit**