



FLOORING & DECKING SOLUTIONS

Mini Mosaic Prime Technical Data Sheet



Product	Mini Mosaic 320mm x 640mm x 8mm Prime
Dimensions	320mm x 640mm x 8mm thick solid European Oak Prime
Grading	Prime grade. No knots. No sap wood. Some colour variation.
Construction	8mm solid European Oak fillets glued to a backing net for installation.
Guarantee	Zimbos Flooring Solutions offers a 5 year guarantee against cracking or buckling of the Oak flooring subject to normal conditions. This means in an environment with a relative humidity of 40 – 60%. This is subject to product being glued down with Wakol MS 228 adhesive, and Wakol PU 280 moisture barrier when concrete screed residual moisture (measured with Concrete Tramex meter) is above 3.5% moisture content.
Formaldehyde	Emission E1
Pentachlorophenol	Emission > 5%

Underfloor heating	Temperature compliant to 25 degrees.
Installation method	Glue down (according to SAWLF specifications)

2 Panther Park, 11 Berkley Road, Maitland, 7405

Tel: +27 21 511 4693

Fax: +27 21 511 4694

www.zimbostrading.co.za

www.loba.co.za

www.wakol.co.za

Reg No: 2002/023222/23

Vat No: 424 019 8855

Members of C.C.: D.O. Waddy & H.A du Toit